



■リードについて
 リードは1回転時の移動距離になります。

リード	1回転時の移動距離
01	1 mm
24	24mm

転造すべりねじ標準品一覧

型式				樹脂ナット寸法						
				外径	全長	フランジ		二面幅	取付穴	
呼び径 D1	リード	ピッチ	条数			D2	A		径 H	厚さ T
4	1	1	1	10	11.5	23	3.5	15	15	2.9
	2	1	2							
6	1	1	1	12	14.5	26	3.5	17	18	3.4
	2	2	1							
	2	2(左ねじ)	1							
	5	2.5	2							
	9	2.25	4							
8	18	4.5	4	14	18	29	4	18	21	3.4
	1	1	1							
	2	2	1							
	2	2(左ねじ)	1							
	6	3	2							
	6	3(左ねじ)	2							
	12	3	4							
	20	5	4							
24	4	6								
10	24	4(左ねじ)	6	16	22	33	5	22	24	4.5
	2	2	1							
	3	3	1							
	3	3(左ねじ)	1							
	6	3	2							
	6	3(左ねじ)	2							
	15	3.75	4							
	24	4	6							
12	30	5	6	18	25	35	6	27	33	4.5
	2	2	1							
	2	2(左ねじ)	1							
	6	3	2							
	6	3(左ねじ)	2							
	12	3	4							
	18	3	6							
36	6	6								
15	45	7.5	6	24	30	42	6	27	33	4.5
	5	5	1							
	10	5	2							
	20	5	4							
	45	7.5(左ねじ)	6							